

Maersk Innovator

Jack-up drilling unit

Owner Maersk Contractors, Denmark
Builder Hyundai Heavy Industries, South Korea
Delivered 2003

Description

Three-legged X-Y cantilever jack-up drilling unit, GustoMSC type CJ70-150-MC.

Classification

Det Norske Veritas
 ✕1A1 Self-elevating drilling unit, DRILL (N), HELDK, CRANES, EO

Main dimensions

Length hull	88.8 m
Breadth hull	102.5 m
Depth hull	11.5 m
Design draft	8.0 m

Survival conditions

Water depth	150 m
Air gap	24 m
Wave height	29 m
Current	1 m/s
Wind speed	49 m/s
Spudcan penetration	3 m

Main tank capacities

Fuel oil	1,779 m ³
Drill water	3,320 m ³
Potable water	508 m ³
Preload	28,212 m ³
Liquid mud	1,558 m ³
Bulk mud	260 m ³
Bulk cement	208 m ³
Brine	757 m ³
Base oil	509 m ³

Variable and combined load

Variable load up to	10,000 t
Combined drilling load:	
• Survival	680 t
• Operating	1,400 t

Legs

Leg length	205 m
Leg diameter	18 m
Spudcan area	380 m ²

Jacking system

Number of pinions	54
-------------------	----



Make	BLM
Type	C170

Fixation system

Make	GustoMSC
Type	9500

Cantilever system

Type	GustoMSC X-Y
Longitudinal reach	27.5 m
Transverse reach	20.0 m

Accommodation

120 persons

Drilling equipment

Drilling depth	9,144 m
Derrick	60 m - 2,000 kips
Draw works	4,600 hp
Top drive	2,000 hp
Well control equipment	15,000 psi HP/HT
Mud pumps	3 x 2,200 hp, 1 x 800 hp

Machinery/ equipment

Main generator sets	4 x 2,700 kW
Deck cranes	3 x 50 t

GustoMSC services

GustoMSC provided the basic design package, including Det Norske Veritas approval. GustoMSC also supplied the fixation and X-Y cantilever skidding systems.

Data presented in this product sheet is for information only. Unit specific specifications as provided by the Owner shall prevail.

The Netherlands

Karel Doormanweg 66, 3115 JD, Schiedam
 P.O. Box 687, 3100 AR Schiedam

Telephone +31 (0)10 232 0800
 Telefax +31 (0)10 232 0801

www.GustoMSC.com